

B. CLAIM AMENDMENTS

Please amend the claims as set forth below. A complete listing of all previously presented claims (claims 1-62) and new claims 63-65 are set forth below. The status of each claim, with markings to show current changes being added to and the matter being deleted from the claims, is presented.

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (CANCELLED).

2. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~1~~7, further comprising an outer casing backing flange, said outer casing backing flange sized and shaped for close fitting engagement over said flanged end of said outer casing.

3. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~1~~7 or in claim 2, wherein said first and second ring portions, when in said closed position, comprise a split ring having a substantially annular ring shape which extends between an outer wall and said interior wall.

4. (ORIGINAL) The apparatus as set forth in claim 3, wherein said split ring further comprises a plurality of longitudinally extending bolt through apertures defined by bolt hole interior walls.

5. (ORIGINAL) The apparatus as set forth in claim 4, further comprising a plurality of fasteners having shaft portions, and wherein said backing flange comprises a plurality of fastener through apertures, wherein each fastener through aperture is defined by an aperture edge wall portion, and wherein said shaft portions of said fasteners are sized and shaped for fitting through one of said fastener through apertures in said backing flange and through a companion axially aligned bolt through aperture in said split ring, and wherein at least one of said plurality of fasteners is adjustably tightenable to secure said backing flange and said split ring each toward the other.

6. (ORIGINAL) The apparatus as set forth in claim 3, wherein eight through apertures are provided in said split ring.

7. (CURRENTLY AMENDED) ~~The apparatus as set forth in claim 1,~~ A slip coupling for engaging a pipe having a longitudinal axis, a smooth outer wall, and an end opening, said slip coupling comprising:

(a) an outer casing, said outer casing having (1) an interior passageway, said interior passageway sized and shaped to fit therein at least some length of said pipe, and (2) a flanged end;

(b) a split ring, said split ring comprising first and second ring portions, said first and second ring portions each having an interior wall, said interior wall further comprising at least one gasket seat, wherein said gasket seat comprises a recess in said interior wall of said first and of said second ring portions, said first and second ring portions adjustably movable between an open position wherein said first and second rings open to allow attachment to or removal from said pipe, and a closed position wherein said first and second ring portions are securable in close fitting engagement around said pipe; and

(c) a gasket, said gasket located at said at least one gasket seat in said inner wall of said first and said second ring portions, said gasket adapted to slidably receive said smooth outer wall of said pipe and to provide a fluid tight seal between said split ring and said smooth outer wall of said pipe.

8. (CURRENTLY AMENDED) The apparatus as set forth in claim 7, wherein said recess comprises an annular groove in said interior sidewall of said first and of said second ring portions.

9. (CURRENTLY AMENDED) The apparatus as set forth in claim 7~~8~~, wherein said first and said second ring portions have an obverse side and a reverse side, and wherein said annular groove is centered between said obverse side and said reverse side.

10. (ORIGINAL) The apparatus as set forth in claim 8, wherein said annular groove has a height H_A extending between a lower groove side and an upper groove side, and wherein said first and

said second ring portions comprise an upper interior body portion above said upper groove side and a lower interior body portion below said lower groove side.

11. (CURRENTLY AMENDED) The apparatus as set forth in claim 109, wherein upper interior body portion extends between said obverse side of said first or of said second split ring portion and said upper groove side of said annular groove, and wherein said upper interior body portion has a thickness H_1 equal to height H_A of said annular groove.

12. (CURRENTLY AMENDED) The apparatus as set forth in claim 109, wherein lower interior body portion extends between said reverse side of said first or of said second split ring portion and said lower groove side of said annular groove, and wherein said lower interior body portion has a thickness H_2 equal to height H_A of said annular groove.

13. (CURRENTLY AMENDED) ~~The apparatus as set forth in claim 1, A~~ slip coupling for engaging a pipe having a longitudinal axis, a smooth outer wall, and an end opening, said slip coupling comprising:

(a) an outer casing, said outer casing having (1) an interior passageway, said interior passageway sized and shaped to fit therein at least some length of said pipe, and (2) a flanged end;

(b) a split ring, said split ring comprising first and second ring portions, said first and second ring portions each having an interior wall, said interior wall further comprising at least one gasket seat, said first and second ring portions adjustably movable between an open position wherein said first and second rings open to allow attachment to or removal from said pipe, and a closed position wherein said first and second ring portions are securable in close fitting engagement around said pipe;

(c) a gasket, said gasket located at said at least one gasket seat in said inner wall of said first and said second ring

portions, said gasket adapted to slidably receive said smooth outer wall of said pipe and to provide a fluid tight seal between said split ring and said smooth outer wall of said pipe; and further comprising

(d) an annular seal, and wherein split ring comprises an obverse side portion, and wherein said flanged end comprises a flange face portion, and wherein said annular seal is sized and shaped for sealing engagement with and compression between said flanged face portion and said obverse side of said split ring.

14. (CURRENTLY AMENDED) ~~The apparatus as set forth in claim 13 or in claim 1, further comprising~~ A slip coupling for engaging a pipe having a longitudinal axis, a smooth outer wall, and an end opening, said slip coupling comprising:

(a) an outer casing, said outer casing having (1) an interior passageway, said interior passageway sized and shaped to fit therein at least some length of said pipe, and (2) a flanged end;

(b) a split ring, said split ring comprising first and second ring portions, said first and second ring portions each having an interior wall, said interior wall further comprising at least one gasket seat, said first and second ring portions adjustably movable between an open position wherein said first and second rings open to allow attachment to or removal from said pipe, and a closed position wherein said first and second ring portions are securable in close fitting engagement around said pipe;

(c) a gasket, said gasket located at said at least one gasket seat in said inner wall of said first and said second ring portions, said gasket adapted to slidably receive said smooth outer wall of said pipe and to provide a fluid tight seal between said split ring and said smooth outer wall of said pipe; and

(d) a compression retainer, said compression retainer circumferentially confining said split ring against radially outward movement.

15. (ORIGINAL) The apparatus as set forth in claim 14, wherein

said compression retainer comprises an adjustably tightenable substantially circular metallic band.

16. (ORIGINAL) The apparatus as set forth in claim 15, wherein said compression retainer comprises a pair of substantially semi-circular metallic band portions, said pair of substantially semi-circular metallic band portions comprising opposing attachment ear portions, said opposing attachment ear portions securable each toward the other by an adjustably tightenable fastener.

17. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~15~~7, wherein said flanged end of said outer casing extends radially outward from said outer casing to an outer end to provide an integral outer casing flange of width sufficient to provide, along a longitudinal axis, a plurality of fastener holes defined by flange interior edge wall holes.

18. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~15~~7, or in claim 17, further comprising a split ring backing flange, said split ring backing flange sized and shaped for close fitting engagement against said split ring.

19. (ORIGINAL) The apparatus as set forth in claim 18, further comprising a plurality of fasteners having shaft portions, and wherein said split ring backing flange comprises a plurality of fastener through apertures, wherein each fastener through aperture is defined by an aperture edge wall portion, and wherein said shaft portions of said fasteners are sized and shaped for fitting through one of said fastener through apertures in said split ring backing flange and through a companion axially aligned bolt through aperture in said split ring, and wherein at least one of said plurality of fasteners is adjustably tightenable to secure said split ring backing flange and said split ring each toward the other.

20. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~15~~7, wherein the material for manufacture of said outer casing is

selected from the group consisting of (a) high density polyethylene, (b) an aluminum alloy, (c) stainless steel, (d) brass, (e) carbon steel, (f) polyvinyl chloride, or (g) a moldable reinforced composite material.

21. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~17~~, wherein the material for manufacture of said split ring is selected from the group consisting of (a) high density polyethylene, (b) an aluminum alloy, (c) stainless steel, (d) brass, (e) carbon steel, (f) polyvinyl chloride, or (g) a moldable reinforced composite material.

22. (ORIGINAL) The apparatus as set forth in claim 18, wherein the material for manufacture of said split ring backing flange is selected from the group consisting of (a) high density polyethylene, (b) an aluminum alloy, (c) stainless steel, (d) brass, (e) carbon steel, (f) polyvinyl chloride, or (g) a moldable reinforced composite material.

23. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~37~~, wherein the material for manufacture of said ~~outer casing backing flange~~flanged end is selected from the group consisting of (a) high density polyethylene, (b) an aluminum alloy, (c) stainless steel, (d) brass, (e) carbon steel, (f) polyvinyl chloride, or (g) a moldable reinforced composite material.

24. (CURRENTLY AMENDED) The apparatus as set forth in claim 23, wherein said ~~outer casing backing flange~~flanged end comprises eight bolt holes defined by edge wall apertures, and wherein said eight bolt holes are equally angularly spaced apart.

25. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~17~~, wherein said first and second ring portions of said split ring are identical.

26. (ORIGINAL) The apparatus as set forth in claim 25, wherein each one of said split ring portions comprises a pair of ear

portions, said ear portions each having a face portion adapted for matching engagement with an identical face portion of another split ring portion.

27. (CURRENTLY AMENDED) ~~The apparatus as set forth in claim 1, A~~
slip coupling for engaging a pipe having a longitudinal axis, a
smooth outer wall, and an end opening, said slip coupling
comprising:

(a) an outer casing, said outer casing having (1) an
interior passageway, said interior passageway sized and shaped to
fit therein at least some length of said pipe, and (2) a flanged
end;

(b) a split ring, said split ring comprising first and
second ring portions, said first and second ring portions each
having an interior wall, said interior wall further comprising at
least one gasket seat, said first and second ring portions
adjustably movable between an open position wherein said first
and second rings open to allow attachment to or removal from said
pipe, and a closed position wherein said first and second ring
portions are securable in close fitting engagement around said
pipe, wherein said first and second split ring portions each
comprise a first arc portion having a first thickness on one side
of said gasket seat, and a second arc portion having a second
thickness on a longitudinally opposite side of said gasket seat,
and wherein said first arc portion is less than one hundred
eighty degrees (180°), and wherein said second arc portion is
more than one hundred eighty degrees (180°); and

(c) a gasket, said gasket located at said at least one
gasket seat in said inner wall of said first and said second ring
portions, said gasket adapted to slidably receive said smooth
outer wall of said pipe and to provide a fluid tight seal between
said split ring and said smooth outer wall of said pipe.

28. (ORIGINAL) The apparatus as set forth in claim 27, wherein
said first arc portion is one hundred fifty degrees (150°), and
wherein said second arc portion is two hundred ten degrees
(210°).

29. (CURRENTLY AMENDED) The apparatus as set forth in claim 1, A slip coupling for engaging a pipe having a longitudinal axis, a smooth outer wall, and an end opening, said slip coupling comprising:

(a) an outer casing, said outer casing having (1) an interior passageway, said interior passageway sized and shaped to fit therein at least some length of said pipe, and (2) a flanged end;

(b) a split ring, said split ring comprising first and second ring portions, said first and second ring portions each having an interior wall, said interior wall further comprising at least one gasket seat, said first and second ring portions adjustably movable between an open position wherein said first and second rings open to allow attachment to or removal from said pipe, and a closed position wherein said first and second ring portions are securable in close fitting engagement around said pipe, wherein said first and second split ring portions each comprise a first arc portion having a first thickness on one side of said gasket seat, and a second arc portion having a second thickness on a longitudinally opposite side of said gasket seat, and wherein said first arc portion and said second arc portion are each one hundred and eighty degrees (180°), and wherein said second arc portion and said first arc portion are angularly offset by a preselected angle alpha (α); and

(c) a gasket, said gasket located at said at least one gasket seat in said inner wall of said first and said second ring portions, said gasket adapted to slidably receive said smooth outer wall of said pipe and to provide a fluid tight seal between said split ring and said smooth outer wall of said pipe.

30. (ORIGINAL) The apparatus as set forth in claim 29, wherein said preselected angle alpha (α) is about thirty degrees (30°).

31. (ORIGINAL) An article of manufacture comprising:

(a) a pipe having a longitudinal axis, a smooth outer wall, and an end opening; and

(b) a slip coupling forming a slidable, pressurizable fluid tight seal with said smooth outer wall of said pipe, said slip coupling comprising

(1) an outer casing, said outer casing having (A) an interior passageway, said interior passageway sized and shaped to fit therein at least some length of said pipe, and (B) a flanged end;

(2) a split ring, said split ring comprising first and second ring portions, said first and second ring portions each having an interior wall, said interior wall further comprising at least one gasket seat, said first and second ring portions adjustably movable between an open position wherein said first and second ring portions open to allow attachment to or removal from said pipe, and a closed position wherein said first and second ring portions are securable in close fitting engagement around said pipe;

(3) a gasket, said gasket located at said at least one gasket seat in said inner wall of said first and said second ring portions, said gasket adapted for providing a fluid tight seal between said split ring and said smooth outer wall of said pipe;

(4) an annular seal, and wherein split ring comprises an obverse side portion, and wherein said flanged end of said outer casing comprises a flange face portion, and wherein said annular seal is sized and shaped for sealing engagement with and compression between said flange face portion and said obverse side of said split ring to provide a fluid tight seal therebetween.

32. (ORIGINAL) The apparatus as set forth in claim 31, further comprising an outer casing backing flange, said outer casing backing flange sized and shaped for close fitting engagement over said flanged end of said outer casing.

33. (ORIGINAL) The apparatus as set forth in claim 31, wherein said flanged end of said outer casing extends radially outward from said outer casing to an outer end to provide an integral

outer casing flange of width sufficient to provide, along a longitudinal axis, a plurality of fastener holes defined by flange interior edge wall holes.

34. (ORIGINAL) The apparatus as set forth in claim 32, or in claim 33, further comprising a split ring backing flange, said split ring backing flange sized and shaped for close fitting engagement against said split ring.

35. (ORIGINAL) The apparatus as set forth in claim 34, wherein said split ring further comprises a plurality of longitudinally extending bolt through apertures defined by bolt hole interior walls.

36. (ORIGINAL) The apparatus as set forth in claim 35, further comprising a plurality of fasteners having shaft portions, and wherein said split ring backing flange comprises a plurality of fastener through apertures, wherein each fastener through aperture is defined by an aperture edge wall portion, and wherein said shaft portions of said fasteners are sized and shaped for fitting through one of said fastener through apertures in said split ring backing flange and through a companion axially aligned bolt through aperture in said split ring, and wherein at least one of said plurality of fasteners is adjustably tightenable to secure (1) said split ring backing flange, (2) said split ring, and (3) either said outer casing backing flange or said integral outer casing flange, whichever is present, together in a leak tight assembly.

37. (ORIGINAL) The apparatus as set forth in claim 36, wherein eight through apertures are provided in said split ring.

38. (CURRENTLY AMENDED) The apparatus as set forth in claim 31 wherein said gasket seat comprises a recess in said interior sidewall of said first and of said second ring portions.

39. (CURRENTLY AMENDED) The apparatus as set forth in claim 38,

wherein said recess comprises an annular groove in said interior sidewall of said first and of said second ring portions.

40. (ORIGINAL) The apparatus as set forth in claim 31, further comprising a compression retainer, said compression retainer circumferentially confining said split ring against radially outward movement.

41. (ORIGINAL) The apparatus as set forth in claim 40, wherein said compression retainer comprises an adjustably tightenable substantially circular metallic band.

42. (ORIGINAL) The apparatus as set forth in claim 41, wherein said compression retainer comprises a pair of semi-circular metallic band portions, said semi-circular metallic band portions also having pairs of opposing attachment ear portions, said opposing attachment ear portions in each pair of opposing attachment ear portions secured each toward the other by an adjustably tightenable fastener.

43. (ORIGINAL) The apparatus as set forth in claim 32, wherein said outer casing backing flange comprises ductile iron.

44. (ORIGINAL) The apparatus as set forth in claim 32, wherein said outer casing backing flange comprises eight bolt holes defined by edge wall apertures, and wherein said eight bolt holes are equally angularly spaced apart.

45. (ORIGINAL) The apparatus as set forth in claim 31, wherein said split ring portions are identical.

46. (ORIGINAL) The apparatus as set forth in claim 45, wherein each one of said split ring portions comprises a pair of ear portions, said ear portions each having a face portion adapted for matching engagement with an identical face portion of another split ring portion.

47. (ORIGINAL) The apparatus as set forth in claim 46, wherein said split ring portions each comprise a first arc portion having a first thickness on one side of said gasket seat, and a second arc portion having a second thickness on a longitudinally opposite side of said gasket seat, and wherein said first arc portion and said second arc portion are each one hundred and eighty degrees (180°), and wherein said second arc portion and said first arc portion are angularly offset by a preselected angle alpha (α).

48. (ORIGINAL) The apparatus as set forth in claim 47, wherein said preselected angle alpha (α) is about thirty degrees (30°).

49. (ORIGINAL) An assembly for collection of landfill gas, said assembly comprising:

(a) a pipe comprising a hollow cylindrical member having smooth outer walls and an upper end;

(b) a slip coupling assembly, said slip coupling assembly comprising

(1) a hollow cylindrical outer casing having an interior cavity, a first open end, and a second flanged end;

(2) an annular seal, said annular seal placed adjacent said flanged end,

(3) a split flange, said split flange positioned adjacent said annular seal so as to compress said annular seal toward said flanged end, said split flange further comprising a gasket seat,

(4) a gasket located in said gasket seat and circumferentially extending around said smooth outer wall of said pipe to form a fluid tight seal therebetween, and

(5) one or more backing rings and a plurality of fasteners to secure (A) said flanged end of said outer casing, (B) said annular seal, (C) said split flange, and (D) said gasket, in a fluid tight relationship.

50. (ORIGINAL) The apparatus as set forth in claim 49, wherein

material of construction for said split flange is selected from the group consisting of (a) high density polyethylene, (b) an aluminum alloy, (c) stainless steel, (d) brass, (e) carbon steel, (f) polyvinyl chloride, or (g) a moldable reinforced composite material.

51. (ORIGINAL) The apparatus as set forth in claim 49, wherein the material of construction for said outer casing is selected from the group consisting of (a) high density polyethylene, (b) an aluminum alloy, (c) stainless steel, (d) brass, (e) carbon steel, (f) polyvinyl chloride, or (g) a moldable reinforced composite material.

52. (ORIGINAL) The apparatus as set forth in claim 49, wherein the material of construction for said pipe is selected from the group consisting of (a) high density polyethylene, (b) an aluminum alloy, (c) stainless steel, (d) brass, (e) carbon steel, (f) polyvinyl chloride, or (g) a moldable reinforced composite material.

53. (ORIGINAL) The apparatus as set forth in claim 49, wherein said slip coupling is slidable along a preselected length of said pipe, and wherein said preselected length is at least two (2) feet.

54. (ORIGINAL) The apparatus as set forth in claim 49, wherein said slip coupling is slidable along a preselected length of said pipe, and wherein said preselected length is at least ten (10) feet.

55. (ORIGINAL) The apparatus as set forth in claim 49, wherein said slip coupling is slidable along a preselected length of said pipe, and wherein said preselected length is forty (40) or more feet.

56. (ORIGINAL) The apparatus as set forth in claim 49, wherein a fluid tight seal is provided which is capable of pressurization.

57. (ORIGINAL) The apparatus as set forth in claim 49, wherein a fluid tight seal is provided capable of withstanding up to one hundred fifty (150) pounds of gas pressure.

58. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~17~~, or in claim 31, or in claim 49, wherein said gasket comprises a resilient material having a coefficient of friction sufficiently low that said gasket remains seated during sliding movement of said gasket over said smooth outer wall of said pipe.

59. (ORIGINAL) The apparatus as set forth in claim 58, wherein said gasket material comprises a fluorolastamer.

60. (ORIGINAL) The apparatus as set forth in claim 59, wherein said fluorolastamer comprises hexafluoropropylene-vinylidene fluoride.

61. (CURRENTLY AMENDED) The apparatus as set forth in claim ~~59~~60, wherein said hexafluoropropylene-vinylidene fluoride comprises a VITON.RTM. brand fluorolastamer.

62. (WITHDRAWN) A method for collection of pressurized landfill gas, said method comprising:

(a) providing a pipe comprising a hollow cylindrical member having smooth outer walls and an upper end;

(b) providing a slip coupling assembly in a fluid tight relationship to said pipe, wherein said slip coupling assembly comprises (1) a hollow cylindrical outer casing having an interior cavity, a first open end, and a second flanged end; (2) an annular seal, said annular seal placed adjacent said flanged end, (3) a split flange, said split flange positioned adjacent said annular seal so as to compress said annular seal toward said flanged end, said split flange further comprising a gasket seat, (4) a gasket located in said gasket seat and circumferentially extending around said smooth outer wall of said pipe to form a fluid tight seal therebetween, and (5) one or more backing rings

and a plurality of fasteners to secure (A) said flanged end of said outer casing, (B) said annular seal, (C) said split flange, and (D) said gasket, in a fluid tight relationship; (c) collecting said landfill gas within said pipe; (d) allowing said landfill gas to traverse through said slip coupling; (e) wherein during traverse of said landfill gas through said slip coupling, said pipe is allowed to move relative to said outer casing, while maintaining a pressurized landfill gas within said pipe.

63. (NEW) A slip coupling for engaging a pipe having a longitudinal axis, a smooth outer wall, and an end opening, said slip coupling comprising:

(a) an outer casing, said outer casing having (1) an interior passageway, said interior passageway sized and shaped to fit therein at least some length of said pipe, and (2) a flanged end;

(b) a split ring, said split ring comprising first and second ring portions, said first and second ring portions each having an obverse side, a reverse side, and an interior wall, said interior wall further comprising at least one gasket seat, said first and second ring portions each further comprising a pair of extending ear portions, said first and second ring portions adjustably movable between an open position, wherein said first and second ring portions open to allow attachment to or removal from said pipe, and a closed position wherein said first and second ring portions are securable in close fitting engagement around said pipe, said ear portions of said first ring portion and said ear portions of said second ring portion configured for close fitting mated engagement when said split ring is in said closed position; and

(c) a gasket, said gasket located at said at least one gasket seat in said inner wall of said first and said second ring portions, said gasket adapted to slidably receive said smooth outer wall of said pipe and to provide a fluid tight seal between said split ring and said smooth outer wall of said pipe.

64. (NEW) The apparatus as set forth in claim 63, wherein each

one of the face portions comprises face portions adapted for matching engagement with an identical face portion of another split ring portion.

65. (NEW) The apparatus as set forth in claim 63, wherein each wherein said gasket seat comprises a recess in said interior wall of said first and of said second ring portions.

CLAIM STATUS

1. Claims 1-62 were pending in this application.
2. Claim 62 is withdrawn as directed to a non-elected method.
3. Claims 2, 3, 7-9, 11-14, 17, 18, 20, 21, 23-25, 27, 28, 29, 38, 39, 58, and 61 have been amended.
 - a. Claims 7, 13, 14, 27, and 29 were amended to place them in independent form, as these claims have been indicated to be allowable. These amendments have not been made to overcome prior art.
 - b. Claims 2, 3, 9, 11, 12, 17, 18, 20, 21, 23, 25, and 58 have been amended to reflect numbering of new parent claims.
 - c. Claims 8, 23, 24, 38, and 39 have been amended to ensure that a proper antecedent basis is provided. These amendments have not been made to overcome prior art.
 - d. Claim 61 has been amended to reflect dependency on a claim including proper antecedent basis. This amendment has not been made to overcome prior art.
4. Claim 1 has been cancelled.
5. Claims 63 - 65 have been added to more fully claim embodiments of the invention.
6. Claims 2-65 are now pending.

RESPONSE

This Amendment is responsive to the Office Action on the merits in this matter, mailed April 25, 2005. In view of the amendments and the remarks made herein, the applicant respectfully requests reconsideration and further examination of this application.